

MSD Saber and Saber Lube Specifications

Model	Excavator Weight 2nd Member		Excavator Weight 3rd Member		Attachment Weight		Jaw Opening		Jaw Depth		Reach (2nd member)	
	Lbs.	M Tons	Lbs.	M Tons	Lbs.	Kg.	in.	mm	ft.	mm	ft.	M
MSD 1000	20,000	9	35,000	16	4,200	1,910	19	482	20	508	5'11"	1.8
MSD 1000R	23,000	10	40,000	18	4,400	2,000	19	482	20	508	8'6"	2.5
MSD 1500	27,000	12	55,000	25	6,600	3,000	22	559	25	635	6'9"	2.1
MSD 1500R	40,000	18	66,000	30	7,000	3,180	22	559	25	635	9'3"	2.8
MSD 2000	42,000	19	70,000	32	8,850	4,020	28	711	29	737	8'3"	2.5
MSD 2000R	50,000	23	90,000	41	10,200	4,636	28	711	29	737	11'0"	3.4
MSD 2000-SL	42,000	19	70,000	32	9,050	4,110	28	711	29	737	8'3"	2.5
MSD 2000R-SL	50,000	23	90,000	41	10,400	4,727	28	711	29	737	11'8"	3.5
MSD 2500	50,000	23	90,000	41	12,000	5,450	32	813	34	864	8'9"	2.7
MSD 2500R	70,000	32	110,000	50	14,600	6,640	32	813	34	864	12'6"	3.8
MSD 2500-SL	50,000	23	90,000	41	12,000	5,450	32	813	34	864	8'9"	2.7
MSD 2500R-SL	70,000	32	110,000	50	14,800	6,730	32	813	34	864	12'6"	3.8
MSD 3000	70,000	32	144,000	65	13,300	6,045	35	889	38	965	9'10"	3.0
MSD 3000R	95,000	43	160,000	73	17,000	7,730	35	889	38	965	14'1"	4.3
MSD 3000-SL	70,000	32	144,000	65	13,500	6,140	35	889	38	965	9'10"	3.0
MSD 3000R-SL	95,000	43	160,000	73	17,200	7,820	35	889	38	965	14'1"	4.3
MSD 4500	90,000	41	160,000	73	17,900	8,140	38.5	978	43	1,092	10'8"	3.3
MSD 4500R	110,000	50	185,000	84	21,000	9,545	38.5	978	43	1,092	14'2"	4.3
MSD 4500-SL	90,000	41	160,000	73	18,100	8,230	38.5	978	43	1,092	10'8"	3.3
MSD 4500R-SL	110,000	50	185,000	84	21,200	9,640	38.5	978	43	1,092	14'2"	4.3
MSD 7500	135,000	61	consult factory		25,500	11,590	43	1092	45	1,143	11'10"	3.6
MSD 7500R	160,000	73	275,000	125	30,000	13,640	43	1092	45	1,143	15'7"	4.7
MSD 7500-SL	135,000	61	consult factory		25,700	11,680	43	1092	45	1,143	11'10"	3.6
MSD 7500R-SL	160,000	73	275,000	125	30,200	13,730	43	1092	45	1,143	15'7"	4.7
MSD 9500	175,000	80	consult factory		37,300	16,950	48	1219	52	1,321	15'4"	4.6
MSD 9500R	275,000	125	consult factory		43,300	19,680	48	1219	52	1,321	18'4"	5.6
MSD 9500-SL	175,000	80	consult factory		37,500	17,050	48	1219	52	1,321	15'4"	4.6
MSD 9500R-SL	275,000	125	consult factory		44,500	20,230	48	1219	52	1,321	18'4"	5.6

Note: Actual weights will vary, depending up options chosen, excavator bracket requirements, etc. All applications must be approved by Stanley Labounty Applications Engineering.